Indicating Valves, Butterfly or Ball Type

Design features provide a dependable visible indication of the open position even at a distance. If excessive force is applied to the handle, weakness-joints will break so as to preserve correct orientation between indicator and valve position. Valve and indicator parts are so designed that they can be assembled only one way, always to give correct indication. All FM Approved indicating valves turn clockwise to shut. They are small, lightweight, and, because of a resilient seat, are easy to operate. They are not subject to sticking or dropped gates. They are not recommended for throttling service. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Models ABV-W300, ABV-G300, ABV-175T

Product Specification

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
ABV-W300	Butterfly Valve, Wafer Body	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a, b, c
ABV-G300	Butterfly Valve, Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300, 76.1, 139.7, 165.1)	300	(2065)	a, b, c
ABV-175T	Butterfly Valve, Threaded Ends	1, 1 1/4, 1 1/2, 2	(25, 32, 40, 50)	175	(1205)	a, b, c, d

Remarks:
a. Available with dual supervisory switches.
b. FM Approved for indoor and outdoor service.
c. FM Approved for aboveground installations only.
d. NPT or BSPT threads

Company Name:	Haci Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
Company Address:	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-Istanbul, Turkey
Company Website:	http://www.ayvaz.com
New/Updated Product Listing:	No
Listing Country:	Turkey
Certification Type:	FM Approved
Class of Work:	1112-Indicating Valves

© 2007-2022 FM Approvals. All rights reserved.