Hose Valves

Hose valves of 1 1⁄2 in. (38 mm) may be used on connections from sprinkler systems; 2 1⁄2 in. (64 mm) valves are used on hose standpipes and fire pump headers. For pressures above 175 psi (1205 kPa), an appropriate pressure reducing device shall be used.

Hose Valves, Angle

Models AHV-100, AHV-200

Product Specification

Model No	Description	Valve Size		Rated Working Pressure	
		in	(mm)	psi	(kPa)
AHV-100	Standard Hose Valve Female NPT x Male NH	1 1/2, 2 1/2	(38, 64)	300	(2065)
AHV-200	Standard Hose Valve Female NPT x Female NPT	1 1/2, 2 1/2	(38, 64)	300	(2065)
AHV-100	Pressure Restricting Hose Valve Female NPT x Male NH	1 1/2, 2 1/2	(38, 64)	300	(2065)
AHV-200	Pressure Restricting Hose Valve Female NPT x Female NPT	1 1/2, 2 1/2	(38, 64)	300	(2065)

Company Name:	Haci Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
Company Address:	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-Istanbul, Turkey
Company Website:	http://www.ayvaz.com
New/Updated Product Listing:	No
Listing Country:	Turkey
Certification Type:	FM Approved
Class of Work:	1521-Angle Hose Valves

© 2007-2022 FM Approvals. All rights reserved.