Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Model NRS-BIG

Resilient Seated Gate Valves. 2 through 24 in. NPS. Valves have a rated working pressure of 250 psi (1725 kPa). Available with the following end connections.

Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
NRS-BIG	2, 2 1/2, 3, 4, 6, 8, 10, 12, 14, 16, 18, 20, 24	(50, 65, 80, 100, 150, 200, 250, 300, 350, 400, 450, 500, 600)	Flange x Flange (ANSI, BS, EN, JIS)

Company Name:	Haci Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
Company Address:	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-Istanbul, Turkey
Company Website:	http://www.ayvaz.com
New/Updated Product Listing:	No
Listing Country:	Turkey
Certification Type:	FM Approved
Class of Work:	1120-OS&Y and NRS Gate Valves

© 2007-2022 FM Approvals. All rights reserved.