


Dimensions







Valve Size	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
	1½	40	2	50	2½	65	3	80	4	100	6	150	8	200
A Threaded	7.25	184	9.38	238	11.00	279	12.50	318	—	—	—	—	—	—
AA 150 ANSI	8.50	216	9.38	238	11.00	279	12.00	305	15.00	381	20.00	508	25.38	645
AAA 300 ANSI	9.00	229	10.00	254	11.62	295	13.25	337	15.62	397	21.00	533	26.38	670
AAAA Grooved End	8.50	216	9.00	228	11.00	279	12.50	318	15.00	381	20.00	508	25.38	645
B Diameter	5.62	143	6.62	168	8.00	203	9.12	232	11.50	292	15.75	400	20.00	508
C Maximum	5.50	140	6.50	165	7.56	192	8.19	208	10.62	270	13.38	340	16.00	406
CC Maximum Grooved End	4.75	120	5.75	146	6.88	175	7.25	184	9.31	236	12.12	308	14.62	371
E	1.12	29	1.50	38	1.69	43	2.06	52	3.19	81	4.31	110	5.31	135
EE Grooved End	2.00	52	2.50	64	2.88	73	3.12	79	4.25	108	6.00	152	7.56	192
F 150 ANSI	2.50	64	3.00	76	3.50	89	3.75	95	4.50	114	5.50	140	6.75	171
FF 300 ANSI	3.06	78	3.25	83	3.75	95	4.13	105	5.00	127	6.25	159	7.50	191
G Threaded	1.88	48	3.25	83	4.00	102	4.50	114	—	—	—	—	—	—
GG 150 ANSI	4.00	102	3.25	83	4.00	102	4.00	102	5.00	127	6.00	152	8.00	203
GGG 300 ANSI	4.25	102	3.50	89	4.31	110	4.38	111	5.31	135	6.50	165	8.50	216
GGGG Grooved End	3.00	76	3.25	83	4.31	110	4.25	108	5.00	127	6.00	152	8.00	203
H NPT Body Tapping	0.375	0.375	0.375	0.375	0.50	0.50	0.50	0.50	0.75	0.75	0.75	0.75	1.00	1.00
J NPT Cover Center Plug	0.25	0.25	0.50	0.50	0.50	0.50	0.50	0.50	0.75	0.75	0.75	0.75	1.00	1.00
K NPT Cover Tapping	0.375	0.375	0.375	0.375	0.50	0.50	0.50	0.50	0.75	0.75	0.75	0.75	1.00	1.00
Stem Travel	0.40	10	0.60	15	0.70	18	0.80	20	1.10	28	1.70	43	2.30	58
Approx. Ship Weight (lbs/kg)	15	7	35	16	50	23	70	32	140	64	285	129	500	227
Approx. **X** Pilot System	11	280	13	331	14	356	15	381	17	432	29	737	31	788
Approx. **Y** Pilot System	9	229	9	229	10	254	11	280	12	305	20	508	22	559
Approx. **Z** Pilot System	9	229	9	229	10	254	11	280	12	305	20	508	22	559

Model Number Codes

B-4KG1

Size
1.5"
2"
2.5"
3"
4"
6"
8"

Main Valve	
50	Globe
2050	Angle

Options	
C	Closing Speed Control
S	Opening Speed Control
P	Pressure Gauges
KOL	Anti-Cavitation Seat
V	X101 Valve Position Indicator

Orientation	
H	Horizontal
V	Vertical

Body	
D	Ductile Iron
C	Cast Steel
T	316 SS
N	N.A.B.
U	Super Duplex
X	Other

Trim	
S	Stainless Steel
T	316 SS (F)
M	Bronze/Monel
U	Super Duplex
X	Other

Pilots	
B	Bronze w/SST
BM	Bronze with Monel Internals
T	316 SS (F)
M	Monel
U	Super Duplex
X	Other

Tubing & Fittings	
B	Copper with Brass Fittings
T	316 SS (F)
M	Monel
U	2507
X	Other

Elastomer	
B	Buna

Flange	
ANSI 150#	
ANSI 300#	
ISO PN10	
ISO PN16	
ISO PN25	
V	Grooved 300#

Face	
RF	
FF	
X	Other

© Copyright CLA-VAL - Specifications subject to change without notice.