
REV	DESCRIPTION	ECN#	DWN	APVD	DATE
A	ISSUED ENGINEERING DRAWING	4407	DTH	JCA	18FEB16
B	ADDED INDUSTRIAL SILENCERS	4407	DTH	JCA	25FEB16
C	DIM A FLANGE ON PG 2 WAS OD IN ERROR	N/A	SAN	JCA	11SEP19
D	REMOVED 1" - 3" & 3.5" SILENCERS	N/A	JCA	JCA	10OCT19


1.50"-4" NPT CONNECTIONS


INDUSTRIAL							RESIDENTIAL							CRITICAL							HOSPITAL						
P/N	A	B	D	E	F	Wgt#	P/N	A	B	C	E	F	Wgt#	P/N	A	B	C	E	F	Wgt#	P/N	A	B	D	E	F	Wgt#
C061306	3.00	NOT AVIALABLE					C061320	3.00	CONSULT FACTORY					C061334	3.00	CONSULT FACTORY					C061348	3.00	CONSULT FACTORY				


4"-12" 150# ANSI FLANGE

INDUSTRIAL								RESIDENTIAL								CRITICAL								HOSPITAL							
	P/N	A	B	C	E	F	Wgt#		P/N	A	B	C	E	F	Wgt#		P/N	A	B	C	E	F	Wgt#		P/N	A	B	C	E	F	Wgt#
*	C061309	4.00	14	30.25	11	5.50	72	*	C061323	4.00	14	39.50	11	5.50	84	*	C061337	4.00	14	55.50	11	6.50	109	*	C061351	4.00	16	56.00	12	6.75	132
*	C061310	5.00	14	39.75	11	7.00	84	*	C061324	5.00	14	63.50	11	7.00	117	*	C061338	5.00	14	68.00	11	7.00	133	*	C061352	5.00	18	69.00	13	7.75	179
*	C061311	6.00	18	45.50	13	8.25	130	*	C061325	6.00	18	57.50	13	8.25	154	*	C061339	6.00	18	68.50	13	8.25	184	*	C061353	6.00	18	78.00	13	8.25	204
*	C061312	8.00	22	46.50	17	9.75	187	*	C061326	8.00	22	69.50	17	9.75	242	*	C061340	8.00	22	81.50	17	9.75	287	*	C061354	8.00	26	93.50	19	10.50	358
*	C061313	10.00	26	59.50	19	11.50	282	*	C061327	10.00	26	89.50	19	11.50	383	*	C061341	10.00	26	106.50	19	11.50	462	**	C061355	10.00	30	108.00	20	12.25	681
*	C061314	12.00	30	73.00	20	13.25	530	**	C061328	12.00	30	109.00	20	13.25	647	**	C061342	12.00	30	120.00	20	13.25	783	**	C061356	12.00	36	122.00	24	14.50	997











DIMENSIONS ARE IN INCHES

* INDICATES ALUMINIZED STEEL

** INDICATES CARBON STEEL





NOTES:

1. DUAL SHELL DESIGN TO ELIMINATE SHELL RADIATED NOISE AND INCREASE DURABILITY.
2. ALUMINIZED/CARBON STEEL CONSTRUCTION.
3. COATED WITH SATIN BLACK PAINT RATED TO 1200°F
4. CONNNECTIONS:
   - -MALE NPT ON 3.0" ONLY
   - -125/150# ANSI FLANGES
5. EQUIPPED WITH PORT PLUGGED DRAIN.
6. ALL WELDED CONSTRUCTION.

THIS DRAWING AND THE INFORMATION HEREON ARE OUR PROPERTY AND MAY BE USED BY OTHERS ONLY AS AUTHORIZED BY US. UNPUBLISHED--ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS

FABRICATION TOLERANCE

DECIMAL mm inch
X ±3
X.X ±1.5 ±0.12
X.XX ±0.06
ANGULAR: ±1.0°

CONTROLLED DRAWING (YES / NO)

CLARKE
Fire Protection Products, Inc.

DRWN	DHAARMEYER
DATE	2/18/2016
ENGR	JAUGENSTEIN
MATERIAL	SEE NOTE 2
ASSEMBLY	SILENCERS
SIMILAR TO	D451

NAME: SILENCER, SPARK ARRESTOR (SIDE INLET, END OUTLET) & (END INLET, END OUTLET)

PART NO.: D734 REV: D

SCALE: NTS UNITS: MM [INCH] PAGE: 1 OF: 2


END INLET, END OUTLET


1.50"-4" NPT CONNECTIONS


	INDUSTRIAL						RESIDENTIAL						CRITICAL						HOSPITAL					
	P/N	A	B	D	Wgt#		P/N	A	B	D	Wgt#		P/N	A	B	D	Wgt#		P/N	A	B	D	Wgt#
	C061386	3.00	NOT AVIALABLE				C061400	3.00	CONSULT FACTORY				C061414	3.00	CONSULT FACTORY				C061428	3.00	CONSULT FACTORY			


4"-12" 150# ANSI FLANGE

	INDUSTRIAL						RESIDENTIAL						CRITICAL						HOSPITAL					
	P/N	A	B	D	Wgt#		P/N	A	B	D	Wgt#		P/N	A	B	D	Wgt#		P/N	A	B	D	Wgt#	
*	C061389	4.00	14	32.00	72	*	C061403	4.00	14	42.00	84	*	C061417	4.00	14	58.50	109	*	C061431	4.00	16	59.00	132	
*	C061390	5.00	14	42.00	84	*	C061404	5.00	14	66.00	117	*	C061418	5.00	14	70.50	133	*	C061432	5.00	18	72.00	179	
*	C061391	6.00	18	49.00	130	*	C061405	6.00	18	61.00	154	*	C061419	6.00	18	72.00	184	*	C061433	6.00	18	80.00	204	
*	C061392	8.00	22	50.00	187	*	C061406	8.00	22	73.00	242	*	C061420	8.00	22	85.00	287	*	C061434	8.00	26	96.00	358	
*	C061393	10.00	26	63.00	282	*	C061407	10.00	26	93.00	383	*	C061421	10.00	26	110.00	462	**	C061435	10.00	30	110.00	681	
**	C061394	12.00	30	76.00	530	**	C061408	12.00	30	112.00	647	**	C061422	12.00	30	123.00	783	**	C061436	12.00	36	126.00	997	











* INDICATES ALUMINIZED STEEL

** INDICATES CARBON STEEL

DIMENSIONS ARE IN INCHES





NOTES:

1. DUAL SHELL DESIGN TO ELIMINATE SHELL RADIATED NOISE AND INCREASE DURABILITY.
2. ALUMINIZED/CARBON STEEL CONSTRUCTION.
3. COATED WITH SATIN BLACK PAINT RATED TO 1200°F
4. CONNNECTIONS:
   - -MALE NPT ON 3.0" ONLY
   - -125/150# ANSI FLANGES
5. EQUIPPED WITH PORT PLUGGED DRAIN.
6. ALL WELDED CONSTRUCTION.

THIS DRAWING AND THE INFORMATION HEREON ARE OUR PROPERTY AND MAY BE USED BY OTHERS ONLY AS AUTHORIZED BY US. UNPUBLISHED--ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS

FABRICATION TOLERANCE

DECIMAL mm inch
X ±3
X.X ±1.5 ±0.12
X.XX ±0.06
ANGULAR: ±1.0°

CONTROLLED DRAWING (YES / NO)

CLARKE
Fire Protection Products, Inc.

DRWN	DHAARMEYER
DATE	2/18/2016
ENGR	JAUGENSTEIN
MATERIAL	SEE NOTE 2
ASSEMBLY	SILENCERS
SIMILAR TO	D451

NAME: SILENCER, SPARK ARRESTOR (SIDE INLET, END OUTLET) & (END INLET, END OUTLET)

PART NO. D734 REV. D

SCALE NTS UNITS MM [INCH] PAGE 2 OF 2