TORNATECH

LISTEN DEVELOP LEAD

GT-FluxFP-A

Orifice Type - Analog Flow Meters

Standard Features

- Nominal size from 2“/ DN 50 to 12“/ DN 300
- Pump rate from 50 - 5 000 USgpm (185 - 19 000 lpm)
- Measuring range from 20 - 10 000 USgpm (75 - 38 000 lpm)
- Easy installation
  - Grooved connection
  - One threaded connection to connect the flow meter display (no tools required)
  - Multi-directional installation of the orifice plate (horizontal, vertical)
- Long lifespan
- Orifice plate can be mounted vertically or horizontally
- Stable flow reading (no bouncing)
- No purging required before using



made in Germany

FM APPROVED

LPCB

LPS 1045: Issue 1.3
LPCB Cert Ref. 1385Ba

Technical Data	
Measuring principle	Orifice plate flowmeter with variable flowmeter as indication
Input • Nominal size	• 2"/DN 50 grooved ends (Ø60.3 mm) • 2½"/DN 65 grooved ends (Ø73.0 mm) • 3"/DN 80 grooved ends (Ø88.9 mm) • 4"/DN 100 grooved ends (Ø114.3 mm) • 6"/DN 150 grooved ends (Ø168.3 mm) • 8"/DN 200 grooved ends (Ø219.1 mm) • 10"/DN 250 grooved ends (Ø273.0 mm) • 12"/DN 300 grooved ends (Ø323.9 mm)
• Operating pressures	• 500 PSI (34.5 bar) from 2" (Ø60.3 mm) to 8" (Ø219.1 mm) • 232 PSI (16 bar) from 10" (Ø219.1 mm) to 12"(Ø323.9 mm)
• Hydrostatically strength/Pressure strength	• 1000 PSI (69 bar) for 5 minutes
Measuring accuracy	• ±2.0 % of full scale value (FM)
Application conditions • Temperature limit • Medium	 • +4 °C to +50 °C (+39 °F to +122 °F) • Water
Design / Material • Orifice plate 2"/DN 50 - 4"/DN 100 6"/DN 150 - 12"/DN 300 • Differential pressure tube • Float • Bypass orifice • Filter • Seal	 • Housing tube in stainless steel with turned grooved connection • Housing tube in coated steel (RAL 3002) with rolled grooved connection[1)] • Brass • Stainless steel • Stainless steel • Stainless steel • NBR
Approval / Certifications	FM Approval & LPCB

[1)] optional in stainless steel with rolled grooved connection

Dimensions and Weights




Fig. 1 GT-FluxFP orifice plate and bypass meter, Drawing and dimensions 2"/DN 50 – 4"/DN 100




Fig. 2 GT-FluxFP orifice plate, Drawing and dimensions 6"/DN 150 - 12"/DN 300

① Housing tube
② Bypass meter
③ Measuring tube
④ Float
⑤ Bypass orifice
⑦ Differential pressure
⑧ O-Ring
⑨ Screw cap
⑩ Cap
⑪ O-Ring
⑫ Seal
⑬ Filter

Normal Size	Dimensions Inch (mm)		Packaging Size Inch (mm)	Weight (Average) incl. packing lbs (kg)
	Length	Diameter (Outside)		
2"/DN 50	3 15/16" (100)	2 3/8" (60.3)	15 (380) x 11 (270) x 10 (250)	4.5 (2.0)
2 1/2"/DN 65	3 15/16" (100)	2 7/8" (73.0)	15 (380) x 11 (270) x 10 (250)	5 (2.1)
3"/DN 80	3 15/16" (100)	3 1/2" (88.9)	15 (380) x 11 (270) x 10 (250)	5.07 (2.3)
4"/DN 100	3 15/16" (100)	4 1/2" (114.3)	15 (380) x 11 (270) x 10 (250)	7.06 (3.2)
6"/DN 150	7 7/8" (200)	6 1/2" (165.1)	15 (380) x 11 (270) x 10 (250)	11 (5.0)
8"/DN 200	7 7/8" (200)	8 5/8" (2191.1)	15 (380) x 11 (270) x 10 (250)	14.11 (6.4)
10"/DN 250	7 7/8" (200)	10 3/4" (273.0)	20 (500) x 14 (350) x 12 (300)	20.06 (9.1)
12"/DN 300	7 7/8" (200)	12 3/4" (323.9)	20 (500) x 14 (350) x14 (350)	24.03 (11)

Description Code

GT-FluxFP - A2 - ☐☐☐☐ ①

1	Model

Nominal Size/Pump Rating

Model	Nominal size grooved ends	Pump rating USgpm	Flow range		Approval / Certifications
			USgpm	LPM	FM / LPCB
0EB0	2"/DN 50 (Ø60.3)	50	20 - 100	75 - 375	✓
0UC0	2½"/DN 65 (Ø73.0)	100	40 - 200	150 - 750	✓
0GD0	3"/DN 80 (Ø88.9)	150	60 - 300	220 - 1 100	✓
0GE0	3"/DN 80 (Ø88.9)	200	80 - 400	300 - 1 500	✓
0HF0	4"/DN 100 (Ø114.3)	250	100 - 500	380 - 1 900	✓
0HG0	4"/DN 100 (Ø114.3)	300	120 - 600	460 - 2 300	✓
0HH0	4"/DN 100 (Ø114.3)	400	160 - 800	600 - 3 000	✓
0HJ0	4"/DN 100 (Ø114.3)	450	180 - 900	680 - 3 400	✓
0KK0	6"/DN 150 (Ø168.3)	500	200 - 1 000	760 - 3 800	✓
0KL0	6"/DN 150 (Ø168.3)	750	300 - 1 500	1 130 - 5 650	✓
0KM0	6"/DN 150 (Ø168.3)	1 000	400 - 2 000	1 500 - 7 500	✓
0KN0	6"/DN 150 (Ø168.3)	1 250	500 - 2 500	1 900 - 9 500	✓
0LP0	8"/DN 200 (Ø219,1)	1 500	600 - 3 000	2 200 - 11 000	✓
0LQ0	8"/DN 200 (Ø219.1)	2 000	800 - 4 000	3 000 - 15 000	✓
0LR0	8"/DN 200 (Ø219.1)	2 500	1 000 - 5 000	3 800 - 19 000	✓
0LS0	8"/DN 200 (Ø219.1)	3 000	1 200 - 6 000	4 500 - 22 500	✓
0MT0	10"/DN 250 (Ø273.0)	3 500	1 400 - 7 000	5 300 - 26 500	✓
0MU0	10"/DN 250 (Ø273.0)	4 000	1 600 - 8 000	6 000 - 30 000	✓
0MV0	10"/DN 250 (Ø273.0)	4 500	1 800 - 9 000	6 800 - 34 000	✓
0NW0	12"/DN 300 (Ø323.9)	5 000	2 000 - 10 000	7 600 - 38 000	✓

AMERICAS
Tornatech Inc.
Head Office
Laval, Quebec, Canada
Tel: + 1 514 334 0523
Toll free: + 1 800 363 8448

EUROPE
Tornatech Europe SA
Mont-Saint-Guibert, Belgium
Tel: + 32 (0) 10 84 40 01

MIDDLE EAST
Tornatech FZE
Dubai, United Arab Emirates
Tel: + 971 (0)4 804 1888

ASIA
Tornatech Pte Ltd.
Singapore
Tel: + 65 6795 8114
Tel: + 65 6795 7823