Sprinklers, Automatic and Open

COMPANY

Viking Corp
5150 Beltway Dr Se
Caledonia, MI 49316 United States

EX643

View model for additional information

Fusible Element Type, SIN(s): VK426, VK427, VK478, VK650, VK651

Fusible Link Type, SIN(s): VK008, VK108, VK110, VK112, VK204, VK206, VK282, VK2843, VK286, VK2883, VK290, VK2923, VK307, VK311, VK316, VK318, VK320, VK326, VK328, VK330, VK332, VK334, VK341, VK343, VK346, VK351, VK353, VK355, VK368, VK469, VK481, VK482, VK483, VK526, VK533, VK535, VK535 (SR), VK537, VK537 (SR), VK551, VK555, VK567, VK592, VK595, VK601, VK601 (SR), VK603, VK603 (SR), VK609, VK609 (SR), VK611, VK613, VK613 (SR), VK636, VK680, VK901

Fusible Link Type, "Sloped Ceilings", SIN(s): VK609 For use below smooth, flat, sloped ceilings with pitches between 2/12 to 4/12 (in./in.) at the minimum flow rates specified. The calculation to determine the design area in accordance with NFPA 13 shall not be credited for the quick response feature and not be debited for installation with slopes with pitches greater than 2/12 (in./in.)

Glass Bulb Type, SIN(s): VK100, VK1001, VK1003, VK102, VK1021, VK1023, VK104, VK116, VK118, VK1181, VK120, VK1201, VK1202, VK122, VK124, VK130, VK132, VK150, VK152, VK154, VK156, VK158, VK162, VK163, VK164, VK166, VK172, VK173, VK174, VK176, VK177, VK178, VK180, VK181, VK182, VK184, VK186, VK186 (SR), VK188, VK188 (SR), VK190, VK192, VK194, VK196, VK196 (SR), VK197, VK200, VK2001, VK2002, VK2003, VK202, VK2021, VK2022, VK2023, VK2503, VK2523, VK2543, VK2753, VK2773, VK2793, VK300, VK3001, VK3003, VK301, VK302, VK3021, VK3023, VK303, VK305, VK310, VK3101, VK315, VK317, VK319, VK325, VK327, VK329, VK331, VK333, VK338, VK339, VK340, VK342, VK344, VK350, VK3501, VK3502, VK3503, VK352, VK3521, VK3522, VK3523, VK354, VK3541, VK3542, VK360, VK377, VK4611, VK462, VK4621, VK464, VK464 (SR), VK4651, VK4921, VK530, VK531, VK532, VK532 (SR), VK534, VK534 (SR), VK536, VK538, VK540, VK550, VK552, VK553, VK554, VK556, VK558, VK560, VK562, VK566, VK570, VK570 (SR), VK572, VK572 (SR), VK580, VK600, VK600 (SR), VK602, VK602 (SR), VK604, VK604 (SR), VK605, VK605 (SR), VK606, VK608, VK608 (SR), VK610, VK612, VK612 (SR), VK617, VK617 (SR), VK618, VK618 (SR), VK630, VK632, VK634, VK638, VK660, VK681, VK682, VK683, VK684, VK685, VK686, VK690, VK693, VK694, VK695, VK696, VK697, VK850, VK851, VK852, VK853, VK900, VK950, VK960, VK962, VK970, VK971, VK972

Glass Bulb Type, "Sloped Ceilings", SIN(s): VK605 For use below smooth, flat, sloped ceilings with pitches between 2/12 to 4/12 (in./in.) at the minimum flow rates specified. The calculation to determine the design area in accordance with NFPA 13 shall not be credited for the quick response feature and not be debited for installation with slopes with pitches greater than 2/12 (in./in.)

Last Updated on 2026-08-24

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."